

---

# MATERIAL SAFETY DATA SHEET

---

## SECTION 1 - IDENTIFICATION OF MATERIAL AND SUPPLIER

---

Product Name: **Silhouette Super Hold Mousse**  
Other Names: Silhouette Super Hold Mousse  
Product Code: 718540 (200g) 718539 (250g)  
Recommended Use: Hair styling

<b>Supplier:</b>	<b>Henkel Australia Pty. Limited</b> <b>135-141 Canterbury Road,</b> <b>Kilsyth, Victoria, 3137</b> <b>AUSTRALIA</b>	<b>Henkel New Zealand Limited</b> <b>106 Springs Road,</b> <b>East Tamaki, Auckland</b> <b>NEW ZEALAND</b>
------------------	---	---

Emergency Telephone Number: 61 2 9978 0666 (9.00 am – 5.00 pm, Monday to Friday) Australia  
0800 930 930 (9.00 am – 5.00 pm, Monday to Friday) New Zealand

---

## SECTION 2 – HAZARDS IDENTIFICATION

---

Not hazardous according to criteria of Worksafe Australia.

### Signal Word:

Warning

### Hazard Classification

2.1.2A Flammable Aerosol  
6.4A Eye Irritant  
9.1D Harmful in the aquatic environment

### Hazard Statements

Extremely Flammable Aerosol  
Cause eye irritation  
Harmful in the aquatic environment

### Precautionary Statements

Read label before use. Keep away from heat/spark/open flames hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container. Do not pierce or burn, even after use.  
Wash hands thoroughly after handling. Wear eye/face protection  
Avoid release to the environment.

### Response Statements

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Apply continuous irrigation with water for at least 15 minutes holding eyelids apart. If eye irritation persists, get medical advice.

### Hazard Statements

Extremely Flammable Aerosol. Can cause eye irritation. Harmful to aquatic life.

### Storage Statements

Protect from sunlight. Do not expose to temperatures exceeding 50°C.

### Classification according to Directive 1999/45/EC (DPD):

F+ - Extremely flammable

---

# MATERIAL SAFETY DATA SHEET

---

R12 Extremely flammable.

**Label elements (DPD):**

F+ - Extremely flammable



**Risk phrases:**

R12 Extremely flammable.

**Safety phrases:**

S33 Take precautionary measures against static discharges.

S60 This material and its container must be disposed of as hazardous waste.

**Additional labeling:**

Keep away from direct sunlight and temperatures over 50°C.

Do not open by force or throw into fire even after use.

Do not spray onto flames or red-hot objects.

Keep away from sources of ignition - no smoking.

Keep out of the reach of children.

**Other hazards:**

None if used properly.

---

## SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

---

Chemical Identity of Ingredients:	CAS Number:	Proportion:
Water	7732-18-5	> 60 %
Ethanol	64-17-5	10 - < 30 %
Butane	106-97-8	< 10 %
Propane	74-98-6	< 10 %
Other cosmetic grade ingredients determined to be non-hazardous	—	to 100%

---

## SECTION 4 – FIRST AID MEASURES

---

Swallowed: Give a glass of water. Contact a doctor or Poisons Information Centre.

Eye: Flush eyes with water. Contact a doctor or Poisons Information Centre if irritation persists.

Skin: Wash skin with soap and water if irritation persists.

Inhaled: If breathing difficulties occur, remove person to fresh air and monitor.

Aggravated medical conditions caused by exposure:

Excessive close contact may cause localised freezing of tissue. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

---

# MATERIAL SAFETY DATA SHEET

---

## SECTION 5 – FIRE FIGHTING MEASURES

---

Suitable extinguishing media: Aerosols are Class 2.1 Dangerous Goods. Aerosols will explode if subjected to temperatures above 50°C. Use water or water-spray extinguishing media to keep containers cool. Product bulk is flammable but water soluble.

Hazards from combustion products: Aerosols represent a fire and explosion hazard. When heated to decomposition, fumes including carbon monoxide and carbon dioxide may be produced.

Special protective precautions and equipment for fire fighters: aerosols will explode at temperatures above 50°C

Hazchem Code: 2YE

---

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

---

Emergency Procedures: Eliminate sources of ignition. Leaking cans may explode. Do not handle distorted cans.

Methods and materials for containment and clean up:

Eliminate ignition sources. For small spills (less than one litre), wipe area with a wet mop/cloth and rinse spill area and cloth with water. For large spills, absorb any escaped liquid with an inert absorbent material (sand, vermiculite). Dispose of waste in accordance with local, state and federal regulations. Collect un-ruptured and undistorted units for assessment by owner.

---

## SECTION 7 – HANDLING AND STORAGE

---

Precautions for safe handling: Keep out of reach of children. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – no smoking. Do not handle distorted cans.

Conditions for safe storage: Keep out of reach of children. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition – no smoking.

Incompatibilities: Temperatures exceeding 50°C. Direct sunlight.

---

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Exposure standards	Chemical Name	TWA *	8hr TWA	15 minute STEL
	Ethanol	1880 mg/m <sup>3</sup>	1000 mg/ m <sup>3</sup>	
	Butane	1900 mg/m <sup>3</sup>	766 mg/ m <sup>3</sup>	958 mg/ m <sup>3</sup>
	Propane	(asphyxiant)		
	* Worksafe Australia Standards			

Biological limit values: Acute Oral LD<sub>50</sub> = 7060 mg/kg(Rat), Inhalation LC<sub>50</sub> = 20 000 ppm/10 Hrs (Rat) (based on 100% Ethanol)

Engineering controls: Use local exhaust ventilation when handling powdered resins. Eliminate ignition sources when mixing or handling liquid bulk. Use aerosols in a well ventilated area, away from all ignition sources. Ensure natural and/or mechanical ventilation (eg. exhaust fan) is adequate to ensure concentrations remain below exposure standards and explosion levels.

Personal protective equipment: Ensure good industrial hygiene practice. Eye protection should be worn when handling bulk product, even if wearing contact lenses. Wear gloves for extended contact with product bulk.

---

---

# MATERIAL SAFETY DATA SHEET

---

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

---

Following properties for product bulk (unless indicated otherwise)

Appearance:	Faun to pale brown, turbid liquid
Odour:	Characteristic odour
pH (at 25°C):	Not applicable
Vapour Pressure (Propellent):	Approximately 400 kPa
Boiling Point:	No data available
Freezing Point:	No data available
Solubility in water:	Soluble
Specific Gravity (at 25°C):	Approximately 1.0 g/mL
Vapour density (Propellant):	Greater than 1.0
Lower explosion limit (Propellent):	1.8%

Product bulk is flammable.

---

## SECTION 10 – STABILITY AND REACTIVITY

---

Chemical stability:	Product bulk is stable under normal conditions. Packaging is stable under normal conditions.
Conditions to avoid:	Nil
Incompatible materials:	Nil
Hazardous decomposition products:	Nil
Hazardous reactions:	None known

---

## SECTION 11 – TOXICOLOGICAL INFORMATION

---

Health effects from likely routes of exposure: no data available

---

## SECTION 12 – ECOLOGICAL INFORMATION

---

Ecotoxicity:	No data available
Persistence and degradability:	No data available
Mobility:	No data available
Environmental Fate:	No data available
Bioaccumulative potential:	No data available

---

## SECTION 13 – DISPOSAL CONSIDERATIONS

---

Disposal methods and containers:	For liquid bulk, contact local EPA for advice. Transport in plastic (polyethylene) lined, sealed drums. For absorbent material used for spill containment, contact local EPA for directions.
Special precautions for landfill or incineration:	Nil

---

# MATERIAL SAFETY DATA SHEET

---

## SECTION 14 – TRANSPORT INFORMATION

---

UN Number: 1950  
UN Proper Shipping Name: AEROSOLS  
Class and subsidiary risk: 2.1  
Packaging Group: Not applicable  
Special precautions for user: Nil  
Hazchem Code: 2YE

---

## SECTION 15 – REGULATORY INFORMATION

---

There is no known regulatory status of this material, or its ingredients, under Australian health, safety or environmental legislation. Furthermore, there is no additional national or international regulatory information.

Approval Code: HSR002552  
Group Name: Cosmetic Products Group Standard  
HSNO Controls: Refer to the EPA website for more information: [www.epa.govt.nz](http://www.epa.govt.nz)

---

## SECTION 16 – OTHER INFORMATION

---

Date of preparation/last revision: 23.02.2015

Acronyms/abbreviations used in this Material Safety Data Sheet:

EPA	Environment Protection Authority
TWA	Time Weighted Averages
STEL	Short Term Exposure Limit

Literature References: Nil

Sources for data: None listed